

SER	SIZE	P.R	LI/SS	Overall Diameter		Section Width		Standard Rim in	Approved Rim Width (in)	Tread Width		Tread Depth		Weight Kg	MAX, PSI Cold	Max Load	
				mm	in	mm	in			mm	in	in32"	mm			KGS	LBS
80	145R12C	8	86/84N	543	21.4	145	5.7	4.0	3.5-5	110	4.3	9	7.5	6.3	65	530 /500	1166/ 1100
	155R12C	8	88/86N	553	21.8	155	6.1	4.5	4-5	112	4.4	10	7.7	7.0	65	560 /530	1232/ 1166
	155R13C	8	90/88N	578	21.8	155	6.1	4.5	4-5	112	4.4	10	7.7	7.5	65	600/560	1320/1166
	165R13C	8	94/92N	599	23.6	165	6.5	4.0	4-5	128	5.0	10	7.9	7.8	65	670/630	1474/1386
	175R13C	8	97/95N	613	24.1	175	6.9	5.0	4.5-6	128	5.0	11	8.4	9.6	65	730/690	1606/1518
	185R14C	8	102/100N	651	25.6	185	7.3	5.5	5-6.5	130	5.1	10	8.3	10.6	65	850/800	1870/1760

MS327 Dimension Data

Above data subject to change without notice.