

SER	SIZE	LI/SS	Overall Diameter		Section Width		Standard Rim	Approved Rim	Tread Width		Tread Depth		Weight	MAX. PSI	Max Load		UTQG
			mm	in	mm	in	in	Width (in)	mm	in	in32"	mm			Kg	Cold	
70	165/70R13	79H	564	22.2	165	6.5	5.0	4-5.5	128	5.0	10	7.8	7.0	36	437	961	200AA
	175/70R13	82H	575	22.6	175	6.9	5.5	4.5-6	134	5.3	10	7.8	7.0	36	475	1045	200AA
	185/70R13	86H	590	23.2	185	7.3	5.5	4.5-6	142	5.6	10	7.9	8.0	36	530	1166	200AA
	165/70R14	81H	589	23.2	165	6.5	5.0	4-5.5	128	5.0	10	7.7	7.4	36	462	1016	200AA
	175/70R14	84H	603	23.7	175	6.9	5.0	4.5-6	140	5.5	10	7.9	8.6	36	500	1100	200AA
	185/70R14	88H	616	24.3	185	7.3	5.5	4.5-6	142	5.6	10	7.9	9.1	36	560	1232	200AA
	195/70R14	91H	630	24.8	195	7.7	6.0	5-6.5	150	5.9	10	8.2	9.8	36	615	1353	200AA
	205/70R14	95H	650	25.6	205	8.1	6.0	5-7	158	6.2	10	8.1	9.8	36	690	1518	200AA
	205/70R14	98H XL	649	26	212	8.0	6.0	5-7	145	6.0	10	8.1	9.5	42	750	1653	350AA
	205/70R15	95H	674	26.5	205	8.1	6.0	5-7	158	6.2	11	8.5	10.4	36	690	1518	200AA

## SS731 Dimension Data

Above data subject to change without notice.